

1 Apache::Status - Embedded interpreter status information

1.1 Synopsis

```
<Location /perl-status>

# disallow public access
Order Deny, Allow
Deny from all
Allow from 127.0.0.1

SetHandler perl-script
PerlHandler Apache::Status
</Location>
```

1.2 Description

The Apache::Status module provides some information about the status of the Perl interpreter embedded in the server.

Configure like so:

```
<Location /perl-status>

# disallow public access
Order Deny, Allow
Deny from all
Allow from 127.0.0.1

SetHandler perl-script
PerlHandler Apache::Status
</Location>
```

Other modules can "plugin" a menu item like so:

```
Apache::Status->menu_item(
    'DBI' => "DBI connections", #item for Apache::DBI module
    sub {
        my ($r,$q) = @_;
        my (@strings);
        push @strings, "blobs of html";
        return \@strings;      #return an array ref
    }
) if Apache->module("Apache::Status"); #only if Apache::Status is loaded
```

WARNING: Apache::Status must be loaded before these modules via the `PerlModule` or `PerlRequire` directives.

1.3 Options

- **StatusOptionsAll**

This single directive will enable all of the options described below.

```
PerlSetVar StatusOptionsAll On
```

- **StatusDumper**

When browsing symbol tables, the values of arrays, hashes and scalars can be viewed via `Data::Dumper` if this configuration variable is set to `On`:

```
PerlSetVar StatusDumper On
```

- **StatusPeek**

With this option *On* and the `Apache::Peek` module installed, functions and variables can be viewed ala `Devel::Peek` style:

```
PerlSetVar StatusPeek On
```

- **StatusLexInfo**

With this option `On` and the `B::LexInfo` module installed, subroutine lexical variable information can be viewed.

```
PerlSetVar StatusLexInfo On
```

- **StatusDeparse**

With this option `On` and `B::Deparse` version 0.59 or higher (included in Perl 5.005_59+), subroutines can be "deparsed".

```
PerlSetVar StatusDeparse On
```

Options can be passed to `B::Deparse::new` like so:

```
PerlSetVar StatusDeparseOptions "-p -SC"
```

See the `B::Deparse` manpage for details.

- **StatusTerse**

With this option *On*, text-based op tree graphs of subroutines can be displayed, thanks to `B::Terse`.

```
PerlSetVar StatusTerse On
```

- **StatusTerseSize**

With this option `On` and the `B::TerseSize` module installed, text-based op tree graphs of subroutines and their size can be displayed. See the `B::TerseSize` docs for more info.

```
PerlSetVar StatusTerseSize On
```

- **StatusTerseSizeMainSummary**

With this option On and the `B::TerseSize` module installed, a "Memory Usage" will be added to the `Apache::Status` main menu. This option is disabled by default, as it can be rather cpu intensive to summarize memory usage for the entire server. It is strongly suggested that this option only be used with a development server running in `-X` mode, as the results will be cached.

```
PerlSetVar StatusTerseSizeMainSummary On
```

- **StatusGraph**

When `StatusDumper` is enabled, another link "OP Tree Graph" will be present with the dump if this configuration variable is set to On:

```
PerlSetVar StatusGraph
```

This requires the `B` module (part of the Perl compiler kit) and `B::Graph` (version 0.03 or higher) module to be installed along with the `dot` program.

`Dot` is part of the graph visualization toolkit from AT&T:
<http://www.research.att.com/sw/tools/graphviz/>).

WARNING: Some graphs may produce very large images, some graphs may produce no image if `B::Graph`'s output is incorrect.

- **Dot**

Location of the `dot` program for `StatusGraph`, if other than `/usr/bin` or `/usr/local/bin`.

- **GraphDir**

Directory where `StatusGraph` should write its temporary image files. Default is `$ServerRoot/logs/b_graphs`.

1.4 Prerequisites

The `Devel::Symdump` module, version **2.00** or higher.

1.5 See Also

`perl`, `Apache`, `Devel::Symdump`, `Data::Dumper`, `B`, `B::Graph`

1.6 Maintainers

Maintainer is the person(s) you should contact with updates, corrections and patches.

- **The documentation mailing list**

1.7 Authors

- **Doug MacEachern**

Only the major authors are listed above. For contributors see the Changes file.

Table of Contents:

1	Apache::Status - Embedded interpreter status information	1
1.1	Synopsis	2
1.2	Description	2
1.3	Options	2
1.4	Prerequisites	4
1.5	See Also	4
1.6	Maintainers	4
1.7	Authors	5