

1 ModPerl::PerlRun - Run unaltered CGI scripts under mod_perl

1.1 Synopsis

```
# httpd.conf
PerlModule ModPerl::PerlRun
Alias /perl-run/ /home/httpd/perl/
<Location /perl-run>
    SetHandler perl-script
    PerlResponseHandler ModPerl::PerlRun
    PerlOptions +ParseHeaders
    Options +ExecCGI
</Location>
```

1.2 Description

META: document that for now we don't `chdir()` into the script's dir, because it affects the whole process under threads. `ModPerl::PerlRunPrefork` should be used by those who run only under prefork MPM.

1.3 Special Blocks

1.3.1 *BEGIN* Blocks

When running under the `ModPerl::PerlRun` handler `BEGIN` blocks behave as follows:

- `BEGIN` blocks defined in scripts running under the `ModPerl::PerlRun` handler are executed on each and every request.
- `BEGIN` blocks defined in modules loaded from scripts running under `ModPerl::PerlRun` (and which weren't already loaded prior to the request) are executed on each and every request only if those modules declare no package. If a package is declared `BEGIN` blocks will be run only the first time each module is loaded, since those modules don't get reloaded on subsequent requests.

See also `BEGIN` blocks in `mod_perl` handlers.

1.3.2 *CHECK and INIT* Blocks

Same as normal `mod_perl` handlers.

1.3.3 *END* Blocks

Same as `ModPerl::Registry`.

1.4 Authors

Doug MacEachern

Stas Bekman

1.5 See Also

`ModPerl::RegistryCooker` and `ModPerl::Registry`.

Table of Contents:

1	ModPerl::PerlRun - Run unaltered CGI scripts under mod_perl	1
1.1	Synopsis	2
1.2	Description	2
1.3	Special Blocks	2
1.3.1	BEGIN Blocks	2
1.3.2	CHECK and INIT Blocks	2
1.3.3	END Blocks	2
1.4	Authors	3
1.5	See Also	3